

Certificate No: TAF00000J3

# TYPE APPROVAL CERTIFICATE

# This is to certify:

That the Class C Division

with type designation(s) **AYRLITE 2054** 

Issued to

# **Ayres Composite Panels** Bayswater WA, Australia

is found to comply with DNV GL offshore standards DNV GL rules for classification - Ships DNV GL statutory interpretations DNVGL-SI-0364 - SOLAS interpretations

## Application:

Approved for use as a class C division and a non-combustible bulkhead. The panel surface is approved as a low flame spread material, not generating excessive quantities of smoke nor toxic products in fire.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

This Certificate is valid until 2022-02-20. Issued at Høvik on 2017-02-21

DNV GL local station: Fremantle

Approval Engineer: Tessa Biever

for DNV GL Digitally Signed By: Hoff, Øyvind Location: DNV GL Høvik, Norway Signing Date: 23.02.2017, on behalf of

> **Petter Langnes** Head of Section

Page 1 of 2 Revision: 2015-05 www.dnvgl.com

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Job Id:

262.1-002119-10

Certificate No: TAF00000J3

#### **Product description**

"AYRLITE 2054"

panel comprising of a non-combustible aluminium honeycomb core with 6.35 mm cell diameter bonded on both sides with aluminium sheets with minimum thickness 0.3 mm, and the front or both sides finished with decorative HPL laminates (maximum thickness 0.4 mm).

Minimum overall panel thickness is 6 mm.

# Application/Limitation

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Any adhesive used other than the one used during testing, has to be tested for low flame spread characteristics according to IMO 2010 FTP Code part 5.

The panels may be regarded as C-class division (Ref. SOLAS II-2 Reg. 3.10 and IMO MSC/Circ. 1120).

Maximum gross calorific value shall be documented separately where applicable, ref. SOLAS Chapter II-2 Reg. 5.3.2.

Each product is to be supplied with its manual for installation and maintenance.

#### Type Approval documentation

Certification in accordance with Class Programme DNVGL-CP-0338, October 2015.

Test Report Nos.:

- PX13977 dated 14 September 2011
- PX18750 and PX18750-1 both dated 13 March 2012
- PX18750-2 dated 14 March 2012

All from SP, Sweden.

#### Tests carried out

Tested according to IMO FTPC Part 2 and 5 and found in compliance with IMO 2010 FTP Code Ch. 8.

The aluminium honeycomb core is tested according to IMO FTPC Part 1 and found in compliance with IMO 2010 FTP Code Ch. 8.

## Marking of product

The product or packing is to be marked with name of manufacturer, type designation and fire rating.

#### Periodical assessment

DNV GL's surveyor is to be given permission to perform Periodical Assessments at any time during the validity of this certificate and at least every second year. The arrangement is to be in accordance with procedure described in Class Programme DNVGL-CP-0338, Section 4.

Form code: TA 1411a Revision: 2015-05 www.dnvgl.com Page 2 of 2